

## SELLING SPECIFICATION

Product :

GAS OIL

Code  
33

This specification meets BS2869: 1998, Class D and the Marketing of Gas Oil (Sulphur Content) Regulations 1994 (Requirements for burner fuels).

PROPERTY	UNITS	MIN	MAX	TEST METHOD
<b>Viscosity, Kinematic at 40C</b>				
Summer (16 March to 30 September inclusive)	mm <sup>2</sup> /s	1.50	5.50	BS EN ISO 3104
Winter (1 October to 15 March inclusive)	mm <sup>2</sup> /s	1.50	5.50	BS EN ISO 3104
Carbon Residue (micro) (10% v/v distillation bottoms)	%m/m		0.30	BS EN ISO 10370
Distillation, recovery at 250C	%v/v		65.0	BS7392
Distillation, recovery at 350C		85.0		BS 7392
Flash Point, closed cup, Pensky-Martens	C	56.0		BS EN 22719
Water Content	mg/kg		200	ASTMD 1744
Sediment	%m/m		0.01	BS EN ISO 3735
Ash	%m/m		0.01	BS EN ISO 6245
Sulphur Content	%m/m		0.20	BS EN SO 8754
Copper Corrosion (3h at 100C) (class)		1		BS EN ISO 2160
<b>Cold filter plugging point</b>				
Summer (16 March to 30September inclusive)	C		-4	BS EN 116
Winter (1 October to 15 March inclusive)			-12	BS EN 116
Strong Acid Number			Zero	BS 2000-139

Additives- Product includes marker dye

From time-to-time at some locations, product may include one or more of the following additives: Anti-static agent, anti-foaming agent, drag-reducing agent and cold improver.